

Display

Brightness (ANSI lumens)	4000
Native Resolution	SVGA (800x600)
Native Aspect Ratio	4:3
Contrast Ratio (FOFO)	20000:1
Display Color	30 Bits (1,07 billion colors)
Light Source	Lamp
Light Source Life	a. Normal 6000 hrs ,b. ECO 10000 hrs ,c. SmartEco 10000 hrs ,d. LampSave 15000 hrs

Optical

Throw Ratio	1.96~2.15
Zoom Ratio	1.1x
Lens	F/# = 2.56 ~ 2.68, f=22~24.1mm
Projection Offset (Full-Height)	110%
Keystone Adjustment	1D, (Auto) Vertical $\pm$ 40 degrees

Picture

Picture Modes	3D ,Bright ,Infographic ,Presentation ,Spreadsheet ,sRGB ,User 1 ,User 2
---------------	--

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB=Reduced blanking
--------------------	---

I/O Interface

PC in (D-sub 15pin)	(x1)
---------------------	------

Monitor out (D-sub 15pin)	(x1)
Composite Video in (RCA)	(x1)
S-Video in (Mini DIN 4pin)	(x1)
HDMI in	(x2) ,HDMI-1 (1.4a/HDCP1.4) ,HDMI-2 (1.4a/HDCP1.4)
USB Type A	(x1)
USB Type Mini B	(x1)
RS232 in (DB-9pin)	(x1)

Audio

Speaker	(x1) ,10W
Audio in (3.5mm Mini Jack)	1
Audio out (3.5mm Mini Jack)	1

Environment

Operating Temperature	0~40°C
Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	260W/110V
Acoustic Noise (Typ./Eco.)(dB)	34/29

Accessories

Carry Bag	Yes,5J.J3T09.001 (optiol)
Remote Control w/ Battery	RCX016
Power Cord (by region)	x1 (1.8M)
VGA(D-sub 15pin) Cable	(Standard) ,1 (1.5m)
3D Glasses	(Optional) ,DGD5

Quick Start Guide	1 (21L)
Warranty Card (by region)	Yes
Universal Ceiling Mount	(Optional) ,Yes, CMG3

Dimension & Weight

Dimensions (WxHxD) (mm)	296 x120 x221
Net Weight (kg)	2.3

Projection System

Projection System	DLP
-------------------	-----